

PINTEK

**HIGH VOLTAGE & HIGH FREQUENCY
OSCILLOSCOPE PROBE**



HVP-15HF

VERY LOW NOISE & HIGH EMS

- MAX. VOLTAGE: 10KVDC/7KVRMS
- BANDWIDTH: DC~40MHz
- DIVISION RATIO: X1000.
- SIGNAL / NOISE: >60dB(1KHz)

PINTEK

HIGH VOLTAGE & HIGH FREQUENCY OSCILLOSCOPE PROBE



HVP-15HF



SPECIFICATION	
MAX.WORKING VOLTAGE	DC : 0~10KV DC AC : pulse $\leq 20KV$ peak to peak AC : Sine wave $\leq 40KV$ rms
SIGNAL / NOISE	$\geq 60dB(1KHz)$, $\geq 50dB(1MHz)$
BANDWIDTH	DC~40MHz(-3dB)
DIVISION RATIO	1 : 1000
RISE TIME	$\leq 8.8ns$
INPUT RESISTANCE	$100M\Omega \pm 1\%$
INPUT CAPACITANCE	$3.0PF \pm 0.5PF$
COMPENSATION RANGE	5PF~50PF
CABLE LENGTH	2.0METER($\pm 0.2M$)
TEMPERATURE COFFICIENT	$\leq 200PPM / ^\circ C$
DC ACCURACY	$\leq 3\%$ DC~10KV
SAFETY APP.	CE, GS, UL, CUL
OPERATING TEMPERATURE	0~50 $^\circ C$
STORAGE TEMPERATURE	-20~+70 $^\circ C$
WEIGHT / VOLUME	250g / $\phi 75*340mmL.$



SALES AGENT



瑞新儀器有限公司
43548 台中市梧棲區建國北街217
巷67號
電話 : 04-2657-0601
傳真 : 04-2657-0621

※Specifications and appearance design subject to change without notice.